1   Inventors: James Hickey; Zamaneh Mowzooni.

2   METHOD AND SYSTEM FOR LOGGING EVENT DATA

3   The present invention generally relates to a method and system

4   for logging event data from at least one operable application program or at least

5   one peripheral device operably connected to a server. More particularly, it

6   relates to a method and system for logging event data that retrieves all the event

7   data for the server, and can maintain a persistent connection when the event

8   data are being downloaded to allow the server to attend to multiple requests

9   resulting in the downloading of event data as they come in.

10   A computer server commonly uses a vast array of application

11   programs and peripheral devices. Each of the application programs and the

12   peripheral devices generally generates event data for events that occur during

13   the operation of the computer server. Events are significant occurrences of a

14   task or program and may relate to matters such as completions, connections,

15   processes, terminations, status changes, errors and warnings. The event data

1   are essential for network diagnostic and troubleshooting. The event data are

2   often used by other application programs and peripheral devices as well.

3   Because of all the different connections and communications

4   between computers that are easily available today, computer troubleshooting is

5   no longer limited to the site of the computer. As a result, there is a need to

6   keep a log of these event data over an extended period of time that can be

7   easily downloaded by users of other computers. However, a typical transfer of

8   a file involves a single request and a single response methodology. In other

9   words, when a file is requested, the two connecting computers will generally

10 terminate their connection once the transfer of the file is complete, which is

11 especially true for a connection over the Internet. Since these event data

12 change rapidly, it would be very useful to be able to keep a persistent

13 connection for downloading the event data file. A persistent connection allows

14 for multiple requests to be served by the server while at the same time

15 permitting the requesting computer to continue downloading the event data as

16 the server continues its operation and new event data comes in.

17 One prior method is to buffer the event data on the server, with

18 periodic requests being made to download the event data. In this method, all

19 the event data are stored on the server's memory, which remain until a request

20 to download is made. Depending on the capacity of the server and the

21 frequency of the downloading, one problem is that some of the event data may

22 have to be discarded. As a result, valuable event data may be lost using this

23 method. Furthermore, that implementation requires servers with significant

24 resources in order to handle busier networks, which may be impracticable for

25 the use of an appliance with an embedded smaller scale server, such as a

26 Hewlett-Packard JetDirect product.

1   Another prior method that establishes a persistent connection

2   through the web is uses Java applets, which establish their own TCP/IP

3   connection to the server and continuously receive the event data. However, a

4   problem with this method is its inflexibility, because it limits the connections to

5   computers that support Java applets. As a result, it is limited to the use of a

6   web connection, and cannot be used with an intranet connection or a direct

7   cable connection. Furthermore, a security certificate is required for a Java

8   applet to establish a network connection, which may not be practical depending

9   on the implementation.

10   Accordingly, a primary object of the present invention is to

11 provide an improved method and system for logging event data that provides a

12 persistent connection for downloading event data.

13   Still another object of the present invention is to provide an

14 improved method and system for logging event data that maintains a log of

15 event data ready for downloading.

16   Yet another object of the present invention is to provide an

17 improved method and system for logging event data that is more flexible and

18 less restrictive.

19   A further object of the present invention is to provide an

20 improved method and system for logging event data that can maintain a

21 persistent connection for downloading while allowing the server to attend to

22 multiple requests and continue logging the event data.

23   SUMMARY OF THE INVENTION

24   The present invention generally relates to a method and system

25 for logging event data from at least one operable application program or at least

26 one peripheral device operably connected to a server. More particularly, it

1   relates to a method and system for logging event data that keeps all the event

2   data for the server and maintains a persistent connection when the event data

3   are being downloaded while allowing the server to attend to multiple requests.

4   In accordance with the present invention, there is provided a

5   method and system for logging event data from at least one operable

6   application program or at least one peripheral device operably connected to a

7   server using a log manager device driver. The method includes the steps of

8   registering the log manager device driver with the server to receive all

9   incoming event data, registering the log manager device driver with the server

10   as a log manager file, the log manager device driver receiving the event data,

11   and the log manager device driver responding to a download request for the log

12   manager file from a requesting computer.

13   Other objects, features and advantages will become apparent

14   upon reading the following detailed description, in conjunction with the

15   attached drawings, in which:

16   FIGURE 1 is a schematic exemplary diagram of a network

17   architecture in which the present method can be implemented;

18   FIG. 2 is a flowchart illustrating a subroutine of the log manager

19   device driver initializing and receiving the event data;

20   FIG. 3 is a flowchart illustrating a subroutine of the log manager

21   responding to a download request for the event data; and,

22   FIG. 4 is a flowchart illustrating a part of the subroutine shown in

23   FIG. 3.

24   DETAILED DESCRIPTION

25   Broadly stated, the present invention is directed to an improved

26   method and system for logging event data in a server that receives all event

27   data ready for downloading to another computer using a persistent connection.

1 A log manager device driver first registers with the server to receive all

2 incoming event data and as the device driver for a log manager file. After the

3 registration with the server, the log manager device driver starts receiving the

4 event data and responding to a download request for the log manager file from

5 a requesting computer.

6 Turning now to FIG. 1, a schematic diagram of an exemplary

7 network architecture is shown, which illustrates one way that the network can

8 be connected for the implementation of the present invention. As shown in

9 FIG. 1, a server 10 is installed with at least one application program 12 (three

10 shown) and connected at least one peripheral device 14 (three shown). A log

11 manager device driver 16 is preferably placed in the server along with the

12 application program 12.

13 In the present invention, a requesting computer 18 seeking to

14 download event data from the server 10 would make a request to download a

15 log manager file 20, which is represented as a regular file and not a device

16 driver file. Since the log manager device driver 16 had registers itself as the

17 log manager file 20 at the startup, the log manager device driver would, in

18 reality, be opened by the requesting computer 18. In practice, the server 10 and

19 requesting computer 18 treat the connection as a download of a very large file.

20 However, the log manager file 20 does not really exist. Rather the request of

21 the file prompts the log manager device driver to return event data to the

22 server, which is sent to the requesting computer as data of the log manager file.

23 As shown in FIG. 1, an event queue 22 is preferably implemented

24 with the log manager device driver 16 for storing event data that has not yet

25 been downloaded. However, the permanent storage of the event data is not

26 necessary. For example, the present invention can be implemented to display

27 the data as it is downloaded from the temporary memory of the server 10. In

5

1   addition, the connection arrangements can be altered.   As an example, a

2   peripheral device 14 need not be connected to the server 10, and the same is

3   true for the application program 12.   These other arrangements and

4   implementations are within the scope of the present invention.

5   Turning now to FIG. 2, a flowchart showing the steps of the log

6   manager device driver 16 initializing and receiving event data from the

7   application program 12 or the peripheral device 14 is shown and generally

8   indicated at 24.   Device drivers comprise software that control hardware

9   components or peripheral devices, such as a magnetic disk, magnetic tape or

10 printer.   At the startup of the computer, the device driver generally registers

11 with the operating system as a device driver for a particular hardware

12 component or peripheral device.

13   For the present invention, at the startup of the server (block 26),

14 the log manager device driver 16 first registers with the server to receive all

15 event data (block 28).   More specifically, the operating system of the server 10

16 is instructed that any time an application program 12 or a peripheral device 14

17 requests to log an event, the event data should be sent to the log manager

18 device driver 16.   Generally, the application programs and the peripheral

19 devices control when and what event data are sent, and the log manager device

20 driver 16 just simply receives the event data.   Next, the log manager device

21 driver 16 registers with the server again, except this time as a device driver for

22 the log manager file 20 (block 30).

23   After all the registrations are made with the server, the log

24 manager device driver 16 then sits idle waiting for event data from the

25 application programs 12 or the peripheral devices 14 (block 32).   Once an

26 application program 12 or a peripheral device 14 sends the event data to the log

27 manager device driver (block 34) and the log manager device driver 16

6

1   receives the event data (block 36), the log manager device driver then

2   determines whether the event queue is full for the newly arrived event data

3   (block 38). If the event queue is full (block 40), the log manager device driver

4   18 deletes the oldest event data in the queue in order to make room (block 42)

5   to save the newly arrived event data in the event queue (block 44). After

6   saving the event data in the queue (block 44, the process loops back to the log

7   manager device driver waiting for more incoming event data (block 32). The

8   receiving event data process is done by the log manager device driver

9   regardless of whether there is a download request initiating the downloading

10 process. In other words, the log manager device driver receives and saves all

11 the event data in the event queue waiting for the requesting computer 18 to

12 download the log manager file 20 from the server 10.

13   Turning now to FIGS. 3 and 4, a flowchart of the subroutine of

14 the log manager device driver responding to a download request of the event

15 data is shown and generally indicated at 46. To initiate this process, a

16 requesting computer 18 must first request a log manager file from the server 10

17 (block 48). The requesting computer 18 then determines whether the server 10

18 received the request to ensure a valid connection between the requesting

19 computer and the server (block 50). If it is determined that the server 10 did

20 not receive the request (block 50), the requesting computer 18 will return an

21 error message (block 52), which is preferably displayed to the user (block 54).

22 On the other hand, if the server 10 did receive the request (block 50), the server

23 will open the log manager file 20 from the log manager device driver 16 (block

24 56).

25   The server next determines whether the log manager file 20 is

26 successfully opened from the log manager device driver (block 58). If the

27 opening of the file proves to be unsuccessful (block 58), the server 10 will

1 return an error message to the requesting computer 18 (block 60), which is

2 again preferably displayed to the user (block 62). If, however, the file is

3 opened successfully, the server reads the event data from the event queue

4 (block 64), and determines whether there are any event data available (block

5 66).

6   If the event queue does not have any event data available (block

7 66), the server blocks, meaning it stays idle and waits, until event data are

8 available in the event queue (block 68). Similarly, the log manager device

9 driver also stays idle and waits for the event data (block 70). When event data

10 are sent from the application program 12 or the peripheral device 14 (block 72),

11 the log manager device driver 16 receives the event data (block 74) and

12 determines whether the event queue is full (block 76). If the queue is full

13 (block 78), the oldest event data in the queue will be deleted to make available

14 space for the newly arrived event data (block 80). Once the event queue 22 has

15 the available space in the event queue (block 78), the log manager device driver

16 16 saves the event data in the queue (block 82).

17   Now that event data is available (block 66), FIG. 4 shows the

18 remaining steps the subroutine from FIG. 3. Referring now to FIG. 4, since

19 event data is available in the queue, the log manager device driver returns the

20 event data in the queue to the server (block 84). The server receives the event

21 data (block 86), and sends it to the requesting computer (block 88). The

22 requesting computer receives the event data from the server (block 90), and

23 preferably displays it to the user immediately or at some point (block 92).

24   It is next determined if the requesting computer wishes to

25 continue downloading the log manager file (block 94). Since the log manager

26 file 20 does not technically exit, in practice the log manager file is a way to

27 maintain the connection between the server 10 and the requesting computer 18.

1 As long as the requesting computer 18 thinks that the downloading of the log

2 manager file 20 is not complete, the connection remains. As a result, a

3 persistent connection is maintained between the server 10 and the requesting

4 computer 18.

5   If the requesting computer 18 wishes to continue downloading

6 the log manager file 20 (block 94), the requesting computer waits for more

7 event data from the server 10 (block 96), and loops the process when the server

8 sends more event data to the requesting computer (block 88). Because the

9 requesting computer thinks that the log manager file is a very large file and the

10 download is incomplete, the connection terminates only when the users choose

11 to end the connection, meaning the computers themselves cannot automatically

12 end the download process. If a user does choose to discontinue downloading

13 the log manager file (block 94), the requesting computer 18 will terminate the

14 connection to the server 10 (block 98). The server will then close the log

15 manager file (block 100), and disconnect from the requesting computer as well

16 (block 102).

17   From the foregoing description, it should be understood that an

18 improved method and system for logging event data has been shown and

19 described which have many desirable attributes and advantages. The method

20 and system allow logging all the event data for a server, which is ready for

21 downloading using a persistent connection. As a result, a more flexible and

22 less restrictive method and system is provided, since the server is able to attend

23 to multiple requests and continue logging the event data during the download

24 process. A user will be able to view the event data as they are created.

25   While various embodiments of the present invention have been

26 shown and described, it should be understood that other modifications,

27 substitutions and alternatives are apparent to one of ordinary skill in the art.

1   Such modifications, substitutions and alternatives can be made without

2   departing from the spirit and scope of the invention, which should be

3   determined from the appended claims.

4   Various features of the invention are set forth in the appended

5   claims.